VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS

Claim 13 has been canceled.

Claims 16 and 17 have been amended as follows:

1	16. (Amended) A semiconductor device as claimed in claim 13, having a semiconductor
2	chip,
3	first electrodes formed on said semiconductor chip,
4	barrier metals formed on said first electrodes and having laminated structures, and
5	a plurality of second protruded electrodes, which serve as external connection terminals,
6	formed on said barrier metals, wherein said barrier metals comprising:
7	a lowermost conductive metal layer laminated on said first electrodes, said lowermost
8	conductive metal layer having a joining property with said first electrodes;
9	an intermediate conductive metal layer laminated on said lowermost conductive metal
10	layer, said intermediate conductive metal layer comprising one or more layers and having a joining
11	property with said lowermost conductive metal layer, said intermediate conductive metal layer
12	having at least one layer serving as a barrier layer for preventing said protruded electrodes from
13	diffusing into said intermediate conductive metal layer; and
14	an uppermost conductive metal layer laminated on said one or more intermediate
15	conductive metal layers, said uppermost conductive metal layer being made of a material which

Serial No. 09/478,508

easily alloys with the material of said intermediate conductive metal layers and which has resistance to oxidation.

16

17

18

19

20

21

wherein said uppermost conductive metal layer is made of a metal selected from the group consisting of gold (Au), platinum (Pt), palladium (Pd), silver (Ag) and rhodium (Rh) or of an alloy containing a metal selected from the group consisting of gold (Au), platinum (Pt), palladium (Pd), silver (Ag) and rhodium (Rh).

17. (Amended) A semiconductor device as claimed in claim 13 16, wherein the weight of said uppermost conductive metal layer is less than 2 weight % of the weight of the bump to be formed thereon.